

### B20 THREE BOLT FIXING ROTATING HALOGEN BEACON


Amber, Polycarbonate Lens. Flash rate : 160 flashes per minute. Operating Temperature -30° to 50°.

#### B20.00.12V/.24V


Less bulb (.LB) versions available .12LB or .24LB. Specify voltage when ordering.

#### Spare Parts

- 10514.00 Amber Lens.
- 27031 Bulb Retaining Clip.
- H448 12V (55W) Halogen Bulb.
- H466 24V (70W) Halogen Bulb.



MOUNTING BOLT ARRANGEMENT



### 320 THREE BOLT FIXING ROTATING HALOGEN BEACON


Amber, Polycarbonate Lens. Flash Rate: 160 flashes per minute. Operating Temperature -30° to 50°.

#### 320.00.LB/.12V/.24V


Specify voltage when ordering.

#### Spare Parts

- 10398.00 Amber Lens.
- 15244.00 Drive Belt.
- 20378.00 Reflector.
- 27031 Bulb Retaining Clip.
- 29211.00 PCB Assembly.
- 13204.00 Motor Module Assembly.
- H448 12V (55W) Halogen Bulb.
- H466 24V (70W) Halogen bulb.



MOUNTING BOLT ARRANGEMENT



### 370 THREE BOLT FIXING ROTATING HALOGEN BEACON


Amber, Flash Rate: 160 flashes per minute. Operating Temperature -30° to 50°

#### 370.00.LB/.12V/.24V

Specify voltage when ordering.

#### Spare Parts

- 10240 Amber Lens.
- 15214 Drive Belt.
- 27031 Bulb Retaining Clip.
- 20285.8 Reflector.
- 13162.00 Motor Module Assembly.
- H448 12V (55W) Halogen Bulb.
- H466 24V (70W) Halogen Bulb.



MOUNTING BOLT ARRANGEMENT

